

Data and Business Rules – Chronic kidney disease (CKD) Indicator Set					
Author	HSCIC - QOF Business Rules team	Version No	30.0	Version Date	10/10/2014

New GMS Contract QOF Implementation

Dataset and Business Rules

-

Chronic Kidney Disease (CKD) Indicator Set

Amendment History:

Version	Date	Amendment History
		The version number starts at 7.1 in order to coincide with existing datasets and business rules.
7.1	21-Nov-2005	From Phil Brown
7.2	22-Nov-2005	Amended following review by Peter Horsfield
7.3	3-Dec-2005	Draft revised for internal review
7.4	23-Feb-2006	Amended following internal & 4 Countries review
8.0	15-Mar-2006	Signed off following 4 Country review
8.1	18-May-2006	Responding to queries raised Amend wording for Note 3
8.5	18-May-2006	Approved by NHSE
8.6	20-Oct-2006	April Read Code Release April SNOMED CT Release October Read Code Release Corrections and amendments following feedback
9.0	30-Nov-2006	Approved by NHSE
9.1	11-Apr-2007	April 2007 Read Code Release
10.0	18-Jun-2007	Signed off following 4 Country review
10.1	20-Aug-2007	April 2007 SNOMED CT Release
10.2	23-Sep-2007	October 2007 Read Code Release October 2007 SNOMED CT Release
10.3	27-Nov-2007	Following 4-Country Review: Remove superfluous 'z' from all instances of G2zz.
11.0	28-Nov-2007	Signed off following 4 Country review
11.1	30-Jun-2008	April 2008 Read Code Release April 2008 SNOMED CT Release QOF Review 2007 (Replace CKD4 with CKD5)
11.2	21-Jul-2008	Following 4-Country Review CKD_COD corrected to reflect the CKD register (stages 3-5) Introduce new CKDPRT cluster (for proteinuria for CKD purposes)
12.0	24-Jul-2008	Signed off following 4 Country review
12.1	06-Oct-2008	October 2008 Read Code Release October 2008 SNOMED CT Release
13.0	05-Dec-2008	Signed off following 4 Country review
31.1	05-Feb-2009	QOF Review 2008
13.2	09-Mar-2009	Amendments following NHSE review
13.3	27_Apr-2009	Amendment following Four-Country Review
14.0	01-May-2009	Sign off following 4 Country review
14.1	25-June-2009	April 2009 Read Code Release
15.0	17-August-2009	Sign off following 4 Country review
15.1	12-October-2009	October 2009 Clinical Code Release
15.2	28-October-2009	October 2009 Clinical Code Release review
16.0	02-December-2009	Sign off following 4 Country review
17.0	07-May-2010	April 2010 Read Code Release following NHS IC review
18.0	29-October-2010	October 2010 Read Code Release following NHS IC review
19.0	13-December-2010	Signed off following 4 Country review
20.0	13-May-2011	April 2011 Read Code Release following NHS

		IC review
21.0	10-November-2011	October 2011 Read Code Release following NHS IC review
22.0	12-December-2011	Signed off following 4 Country review
23.0	31-May-2012	April 2012 Read Code Release following HSCIC review
24.0	31-October-2012	October 2012 Read Code Release following HSCIC review
25.0	28-March-2013	Signed off following consultation
26.0	01-June-2013	April 2013 Read Code Release following HSCIC review
27.0	25-October-2013	October 2013 Read Code Release following HSCIC review
Dates_1415	17-January-2014	Review of proposed date changes for QOF 2014/15
Jan14_Review	23-January-2014	Internal review of changes for 2014/15
28.0	28-March-2014	Signed off following review and negotiations. Changes made to incorporate new date terminology
29.0	27-June-2014	April 2014 Read Code Release following HSCIC review
30.0	10-October-2014	October 2014 Read Code Release following HSCIC review

This document is produced by HSCIC on behalf of NHS England. It is published in PDF format. If anyone intends to re-use the information contained within it or publish in another format then they should acknowledge the source document, HSCIC and NHS England.

New GMS contract Q&O framework implementation

Dataset and business rules – Chronic Kidney Disease (CKD) indicator set

Notes

- 1) QOF has been in operation since 2003 as the landscape within the NHS and Primary Care changes, the QOF dataset and rulesets must change in accordance with that new landscape. QOF is categorised as one of many Quality Services and a Quality Service has a start date (Quality Service Start Date) and an end date (Quality Service End Date). For QOF these reflect the QOF Year (i.e. 1st April to 31st March).
- 2) The specified dataset and rulesets are to support analysis of extracted data to reflect the status at a specified point in time of patient records held by the practice. In the context of this document that specified time point is designated the use of a number of dates. The dates are as follows
 - a) **ACHIEVEMENT_DAT**: The date up to which patient information is considered when determining the output for each extraction.
 - For QOF 2014/15, **ACHIEVEMENT_DAT** will vary for each extraction depending on the reporting period for that extraction, e.g. for the end of **September extraction** it would have a value of **30.09.2014**; for the end of **March extraction** it would have a value of **31.03.2015**.
 - b) **PAYMENTPERIODEND_DAT**: The end date of the period for which payments are made for a given Quality Service. For any given Quality Service there will be one or more payment periods.
 - For QOF 2014/15, **PAYMENTPERIODEND_DAT** is **31.03.2015**
 - c) **QUALITY_SERVICE_START_DAT (QSSD)**: The start of the period during which a GP Practice provides the Quality Service
 - For QOF 2014/15, **QUALITY_SERVICE_START_DAT (QSSD)** is **01.04.2014**, however it is not utilised within the QOF dataset and rulesets.
 - d) **QUALITY_SERVICE_END_DAT (QSED)**: The end of the period during which a GP Practice provides the Quality Service
 - For QOF 2014/15, **QUALITY_SERVICE_END_DAT (QSED)** is **31.03.2015**
- 3) When interpreting these dates midnight is to be taken as meaning
 - a) **for the 'start of a period'**: the midnight is at the start of that day, For example; **"If CSMOK_DAT > (PAYMENTPERIODEND_DAT – 24 months)"**
This example is used to determine if a code has been recorded in the 24 months preceding end of the payment period. If PAYMENTPERIODEND_DAT has a value of 31.03.2015, then this condition uses a value of 31.03.2013, but to be true the recorded code must be **after** 31.03.2013 and therefore this equates to the midnight between 31.03.2013 and 01.04.2013. This means information effective on 31st March will be excluded but information effective on 1st April will be included for the extraction.
 - b) **for the 'end of a period'**: the midnight at the end of that day, For example; **"Earliest <= ACHIEVEMENT_DAT"**
This example is used to determine if a recorded code has been recorded before the achievement date. If ACHIEVEMENT_DAT has a value of 30th September (i.e. the end of September extraction) then this condition uses a value of 30.09.2014, but to be true the recorded code must be **on or before** 30.09.2014 and therefore this equates to the midnight between 30.09.2014 and 01.10.2014. This means information effective on 30th September will be included but information effective on 1st October will be excluded from the extraction.

- c) **for Patient Age:** the midnight at the end of that day, For example;
"Patients age (years) at ACHIEVEMENT_DAT"

This example is used to determine a patients age, in years, at the achievement date. If ACHIEVEMENT_DAT has a value of 30th September (i.e. the end of September extraction) then this condition determines a patient age as of 30.09.2014. Therefore this equates to the midnight between 30.09.2014 and 01.10.2014.

- 4) To support accurate determination of the population of patients to which the indicators should relate (the denominator population) these rulesets have been compiled with a prior all of the dates (described in point 2 above) are specified prior to extraction of data and are available for computation in the data extraction routine. The dates are required to be included in the data extraction to support processing of rules that are dependent upon them. It is possible that an alternative approach could be adopted in which rules to determine the denominator population by registration status would be applied as a component of rule processing. If this second approach were to be adopted it would be essential to specify default time criteria for determining the registration characteristics of the denominator population during the data extraction process. Additionally there would be a requirement to supplement the dataset and rulesets to support identification of the appropriate denominator population.
- 5) Clinical codes quoted are (where known) from the October 2014 release of Read codes version 2 and clinical terms version 3 (CTV3). The codes are shown within the document as a 5 character value to show that the Read Code is for a 5-Byte system.
- i) Where a '%' wildcard is displayed, the Read Code is filled to 5 characters with full-stops. When implementing a search for the Read Code, only the non full-stop values should be used in the search, For example, a displayed Read Code of c1...% should be implemented as a search for c1%, i.e. should find c1 and any of it's children.
 - ii) Where a range of read codes are displayed, the Read Code is filled to 5 characters with full-stops. When implementing the search, only the non full-stop values should be used in the search, For example, a displayed Read Code range of G342. – G3z.. should find all codes between G342 and G3z (including any children where applicable).

The version number starts at 7.1 in order to coincide with existing datasets and business rules.

- 6) Datasets comprise a specification of two elements:
- a) Patient selection criteria. These are the criteria used to determine the patient population against whom the indicators are to be applied.
 - i) Registration status. This determines the current patient population at the practice
 - ii) Diagnostic code status. This determines the current patient population (register size) for a given clinical condition

There are three scenarios within the diagnostic code status, these are where

- There is a single morbidity patient population (disease register) required (e.g. within CHD). Where this occurs, a single set of rules for identifying the patient population is provided.
- There is a single co-morbidity patient population (disease register) required (e.g. within Smoking). Where this occurs, a set of rules for **each** morbidity is provided. A patient **must** only be included in the patient population (register size) **once**.

- There are multiple patient populations (disease registers) required (e.g. within Heart Failure). Where this occurs, a single set of rules for **each** patient population is provided.
N.B. where there are multiple patient populations (disease registers), it is possible that one or more will also be a co-morbidity patient population (e.g. within Depression)

Where this occurs, details of which register population applies to which indicator(s) are provided. Where the register size applies to an indicator, this is the base denominator population for that indicator.

- b) Clinical data extraction criteria. These are the data items to be exported from the clinical system for subsequent processing to calculate points allocations. They are expressed in the form of a MIQUEST 'Report-style' extract of data.

The record of each patient that satisfies the appropriate selection criteria for a given indicator will be interrogated against the clinical data criteria (also appropriate to that indicator). A report of the data contained in the selected records will be exported in the form of a fixed-format tabular report. Each selected patient will be represented by a single row in the report, unless the operator "ALL" is used.

The "ALL" statement is used within the Qualifying Criteria for the Clinical data extraction criteria. Typically the selection for a READCODE_COD cluster field is based on a date of "LATEST" or "EARLIEST". The "ALL" statement is used to select all occurrences of any of the codes within the READCODE_COD cluster. It selects an array of instances, of which there may be more than one for each patient.

Rows will contain a fixed number of fields each containing a single data item. The number of fields in each row and their data content will be determined by the clinical data criteria. Data items that match the clinical data criteria will be exported in the relevant field of the report. Where there is no data to match a specific clinical criterion a null field will be exported.

- 7) Rulesets are specified as multiple rules to be processed sequentially. Processing of rules should terminate as soon as a 'Reject' or 'Select' condition is encountered
- 8) Rules are expressed as logical statements that evaluate as either 'true' or 'false'. The following operators are required to be supported:
- | | |
|---------------------|--------|
| a) > (greater than) | e) AND |
| b) < (less than) | f) OR |
| c) = (equal to) | g) NOT |
| d) ≠ (not equal to) | |
- 9) Where date criteria are specified with intervals of multiples of months or years these should be interpreted as calendar months or calendar years.

Dataset Specification

1) Patient selection criteria:

a) Registration status

<u>Current registration status</u>	<u>Qualifying criteria</u>
Currently registered for GMS	Most recent registration date <= (ACHIEVEMENT_DAT)
Previously registered for GMS	Any sequential pairing of registration date and deregistration date where both of the following conditions are met: registration date <= (ACHIEVEMENT_DAT); and deregistration date > (ACHIEVEMENT_DAT)

b) Diagnostic code status

<i>Code criteria</i>	<i>Qualifying diagnostic codes</i>		<i>Time criteria</i>
<i>Included</i>	<i>Read codes v2</i>	<i>CTV3</i>	<i>Latest <= (ACHIEVEMENT_DAT)</i>
	1Z12. 1Z13. 1Z14. 1Z15. 1Z16. 1Z1B. - 1Z1L. K053. K054. K055.	XaLHI% XaLHJ% XaLHK%	
	<i>(Chronic kidney disease codes 3-5)</i>		
<i>Excluded</i>	<i>Read codes v2</i>	<i>CTV3</i>	<i>Latest <= (ACHIEVEMENT_DAT) AND > Date of diagnostic code above</i>
	1Z10. 1Z11. 1Z17. - 1Z1A. K051. K052.	XaLHH% XaLHG%	
	<i>(Chronic kidney disease codes 1-2)</i>		
<i>Excluded</i>	<i>Age < 18 yrs at ACHIEVEMENT_DAT</i>		

2) Clinical data extraction criteria

<u>Field Number</u>	<u>Field name</u>	<u>Data item</u>		<u>Qualifying criteria</u>
1	PAT_ID	Patient ID number		Unconditional
2	REG_DAT	Date of patient registration		Latest <= (ACHIEVEMENT_DAT)
3	CKDEXC_COD	<i>Read codes v2</i>	<i>CTV3</i>	Latest <= (ACHIEVEMENT_DAT)
		9hE1. 9hE0.	XaLFn XaLFm	
		<i>(Chronic kidney disease exception reporting codes)</i>		
4	CKDEXC_DAT	Date of CKDEXC_COD		Chosen record
5	CKD_COD	<i>Read codes v2</i>	<i>CTV3</i>	Latest <= (ACHIEVEMENT_DAT)
		1Z12. 1Z13. 1Z14. 1Z15. 1Z16. 1Z1B. - 1Z1L. K053. K054. K055.	XaLHI% XaLHJ% XaLHK%	
		<i>(Chronic kidney disease codes 3-5)</i>		
6	CKD_DAT	Date of CKD_COD		Chosen record
7	BP_COD	<i>Read codes v2</i>	<i>CTV3</i>	Latest <= ACHIEVEMENT_DAT
		246..% (excluding 2460.,2468., 246H., 246I., 246K., 246L., 246M., 246h., 246i., 246j., 246k.)	X773t% (excluding XaI9f, XaI9g, X779b, X779R, X779T, X779W, XaYai, XaYg8, XaYg9)	

			246..% (excluding 2460., 2468., XaCFN, XaCFO, XaZvo, XaZxj)	
		<i>(BP recording codes)</i>		
8	BP_DAT	Date of BP_COD		Chosen record
9	BP_SYS	Value 1 of BP_COD <i>(Systolic BP value)</i>		Chosen record
10	BP_DIA	Value 2 of BP_COD <i>(Diastolic BP value)</i>		Chosen record
11	BPEX_COD	<i>Read codes v2</i>	CTV3	Latest <= ACHIEVEMENT_DAT
		8I3Y.	XaJkR	
		<i>(BP recording exception codes)</i>		
12	BPEX_DAT	Date of BPEX_COD		Chosen record
13	HTMAX_COD	<i>Read codes v2</i>	CTV3	Latest <= ACHIEVEMENT_DAT
		8BL0.	XaJ5h	
		<i>(Code for maximal BP therapy)</i>		
14	HTMAX_DAT	Date of HTMAX_COD		Chosen record
15	HYP_COD	<i>Read codes v2</i>	CTV3	Latest <= ACHIEVEMENT_DAT
		G2... G20..% G24..- G2z.. (Excluding G24z1, G2400, G2410, G27..) Gyu2. Gyu20	XE0Ub XE0Uc% G24..% (excluding 61462, G2400, G2410, G24z1, Gyu21, L1282, Xa0kX) G2...% Xa0Cs XSDSb G202. Xa3fQ XaZWn XaZbz	

			XaZWm Xab9M Xab9L	
		<i>(Hypertension diagnosis codes)</i>		
16	HYP_DAT	Date of HYP_COD		Chosen record
17	HYPRES_COD	<i>Read codes v2</i>	CTV3	Latest <= (ACHIEVEMENT_DAT) AND > HYP_DAT
		21261 212K.	21261	
		<i>(Codes for hypertension resolved)</i>		
18	HYPRES_DAT	Date of HYPRES_COD		Chosen record
19	XACE_COD	<i>Read codes v2</i>	CTV3	Latest <= ACHIEVEMENT_DAT
		14LM. U60C4 TJC77 - TJC79 ZV14D K0430	XaJ5y XaJ8Y Xa60w% Xa5cT% XaIrq U60C4 TJC77 TJC78 TJC79 X70wH XaZ6J	
		<i>(Ace inhibitor contraindications; persistent)</i>		
20	XACE_DAT	Date of XACE_COD		Chosen record
21	TXACE_COD	<i>Read codes v2</i>	CTV3	Latest <=

		8I28. 8I3D. 8I64. 8I74.	XaG2W XaIIm XaIIf XaJ5e	ACHIEVEMENT_DAT
		<i>(Ace inhibitor contraindications; expiring)</i>		
22	TXACE_DAT	Date of TXACE_COD		Chosen record
23	XAII_COD	<i>Read codes v2</i>	<i>CTV3</i>	Latest <= ACHIEVEMENT_DAT
		14LN. U60CB ZV14E	XaJ5z XaJ8o XaIzK XaJ8W Xa619 Xa5cg	
		<i>(AII antagonist contraindications: persisting)</i>		
24	XAII_DAT	Date of XACE_COD		Chosen record
25	TXAII_COD	<i>Read codes v2</i>	<i>CTV3</i>	Latest <= ACHIEVEMENT_DAT
		8I2H. 8I3P. 8I6C. 8I75.	XaInW XaIyw XaJ5m XaJ5f	
		<i>(AII antagonist contraindications: expiring)</i>		
26	TXAII_DAT	Date of TXAII_COD		Chosen record
27	ACE_COD	<i>Read codes v2</i>	<i>CTV3</i>	Latest <=

		bi...% bA...% bk6..%	bi...% bA...%	ACHIEVEMENT_DAT
		<i>(Ace inhibitor prescription codes)</i>		
28	ACE_DAT	Date of ACE_COD		Chosen record
29	AII_COD	<i>Read codes v2</i>	<i>CTV3</i>	Latest <= ACHIEVEMENT_DAT
		bk3.. - bk5z. bk7.. - bk9z. bkB..%, bkC..%, bkD..% bkH..%, bkI..% bkJ..%	x03j2% x03ls% bkD..% bkH..% bkI..% bkJ..%	
		<i>(AII antagonist prescription codes)</i>		
30	AII_DAT	Date of AII_COD		Chosen record
31	CKDPRT_COD	<i>Read codes v2</i>	<i>CTV3</i>	Latest <= (ACHIEVEMENT_DAT)
		1Z1B. 1Z1D. 1Z1F. 1Z1H. 1Z1K. R110. R1100 R1103 R110z	XaO3t XaO3v XaO3x XaO3z XaO41 R110. R1100 XaE6q R110z	
		<i>(Codes for proteinuria for CKD)</i>		

32	CKDPRT_DAT	Date of CKDPRT_COD		Chosen record
33	APCR_COD	<i>Read codes v2</i>	<i>CTV3</i>	Latest <= (ACHIEVEMENT_DAT)
		44ID. 44IzX 46TC. 46TD.	XaEMS XabrL XE2n3 XE2n4	
		<i>(Codes for Albumin:Creatinine & Protein:Creatinine Ratio for CKD)</i>		
34	APCR_DAT	Date of APCR_COD		Chosen record
35	URINEEXC_COD	<i>Read codes v2</i>	<i>CTV3</i>	Latest <= (ACHIEVEMENT_DAT)
		9RX..	Xaa3v	
		<i>(Codes for declined to give urine specimen)</i>		
36	URINEEXC_DAT	Date of URINEEXC_COD		Chosen record

Indicator rulesets

- 1 Indicator CKD001: The contractor establishes and maintains a register of patients aged 18 or over with CKD (US National Kidney Foundation: Stage 3 to 5 CKD)

The terms of this indicator will be satisfied if the practice is able to produce a data extraction according to the above criteria.

No numerator or denominator determination is required.

- 2 Indicator CKD002: The percentage of patients on the CKD register in whom the last blood pressure reading (measured in the preceding 12 months) is 140/85 mmHg or less.

a) Denominator ruleset

<i>Rule number</i>	<i>Rule</i>	<i>Action if true</i>	<i>Action if false</i>
1	If <u>BP_SYS</u> <= 140 AND If <u>BP_DIA</u> <= 85 AND If <u>BP_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 12 months)	Select	Next rule
2	If <u>BPEX_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 12 months)	Reject	Next rule
3	If <u>REG_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 9 months)	Reject	Next rule
4	If <u>CKDEXC_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 12 months)	Reject	Next rule
5	If <u>CKD_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 9 months)	Reject	Next rule
6	If <u>HTMAX_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 12 months)	Reject	Select

b) Numerator ruleset: To be applied to the above denominator population

<i>Rule number</i>	<i>Rule</i>	<i>Action if true</i>	<i>Action if false</i>
1	If <u>BP_SYS</u> <= 140 AND If <u>BP_DIA</u> <= 85 AND If <u>BP_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 12 months)	Select	Reject

- 3 Indicator CKD003: The percentage of patients on the CKD register with hypertension and proteinuria who are currently treated with an ACE-I or ARB

a) Denominator ruleset

<i>Rule number</i>	<i>Rule</i>	<i>Action if true</i>	<i>Action if false</i>
1	If <u>HYP_DAT</u> ≠ Null AND If <u>HYPRES_DAT</u> = Null	Next rule	Reject
2	If <u>CKDPRT_DAT</u> = Null	Reject	Next rule
3	If <u>ACE_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 6 months) OR If <u>AII_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 6 months)	Select	Next rule
4	If <u>REG_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 3 months)	Reject	Next rule
5	If <u>CKDEXC_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 12 months)	Reject	Next rule
6	If <u>CKD_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 3 months)	Reject	Next rule
7	If <u>XACE_COD</u> = Null AND If <u>TXACE_DAT</u> = Null	Select	Next rule
8	If <u>XACE_COD</u> = Null AND If <u>TXACE_DAT</u> <= (<u>PAYMENTPERIODEND_DAT</u> – 12 months)	Select	Next rule
9	If <u>XAII_COD</u> = Null AND If <u>TXAII_DAT</u> = Null	Select	Next rule
10	If <u>XAII_COD</u> = Null AND If <u>TXAII_DAT</u> <= (<u>PAYMENTPERIODEND_DAT</u> – 12 months)	Select	Reject

b) Numerator ruleset: To be applied to the above denominator population

<i>Rule number</i>	<i>Rule</i>	<i>Action if true</i>	<i>Action if false</i>
1	If <u>ACE_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 6 months) OR If <u>AII_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 6 months)	Select	Reject

- 4 Indicator CKD004: The percentage of patients on the CKD register whose notes have a record of a urine albumin:creatinine ratio (or protein:creatinine ratio) test in the preceding 12 months.

The negotiating parties have confirmed that the majority of pathology laboratories in the UK have the capability and capacity to provide these tests.

a) Denominator ruleset:

<i>Rule number</i>	<i>Rule</i>	<i>Action if true</i>	<i>Action if false</i>
1	If <u>APCR_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 12 months)	Select	Next rule
2	If <u>URINEEXC_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 12 months)	Reject	Next rule
3	If <u>REG_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 3 months)	Reject	Next rule
4	If <u>CKDEXC_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 12 months)	Reject	Next rule
5	If <u>CKD_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 3 months)	Reject	Select

b) Numerator ruleset: To be applied to the above denominator population

<i>Rule number</i>	<i>Rule</i>	<i>Action if true</i>	<i>Action if false</i>
1	If <u>APCR_DAT</u> > (<u>PAYMENTPERIODEND_DAT</u> – 12 months)	Select	Reject